

PowerScan™

Industrial Bar Code Scanner



Ideal For:

- Warehousing & Outdoor use
- Transportation & Logistics
- Package Distribution
- Electronic Assembly
- Heavy-Duty Manufacturing

Features:

- QuadraLogic™ II decoding software for superior scanning performance
- Multi-interface modules provide ultimate flexible connectivity
- Positive trigger feedback for gloved hand operation
- Integrated metal tether hook
- Programmable scan angle, beeper tone, & volume
- Field upgradable Flash Memory
- Flexible mounting and storage accessories available

A Tough Tool For Your Toughest Jobs

PowerScan™: Setting a New Standard

The PowerScan family of handheld laser bar code scanners has been specifically designed "from the ground up" to meet the demands of industrial users. In this tough environment, the right tool makes all the difference. With a PSC PowerScan scanner on the job, you'll have one of the toughest, most reliable tools around.

You can rely on the PowerScan scanner for fast, accurate bar code reading, from up close to over 60' / 152 cm away. Even labels previously thought to be unreadable can now be read using PSC's superior decoding software, QuadraLogic™ II. The scanner will autodiscriminate all standard bar code symbologies and automatically adjusts to read a wide range of code densities.

Dependable In The Harshest Conditions

Even in the most harsh working environments, you can depend on the PowerScan scanner to keep on working. Designed to meet the most stringent drop specification in the industry, the scanner will withstand multiple 6.5' / 2 m drops to concrete. Even dust and moisture won't phase it. In fact, the PowerScan scanner has a rating of IP54, which means it meets or exceeds the sealing rating of every portable host terminal on the market. And don't worry about weather conditions – the PowerScan scanner operates over a wide temperature range, from below freezing to over 122° F / 50° C.

Built To Stand Up To Abuse

Handheld scanners often are dropped and abused, so this scanner has been designed with high impact-resistant material and incorporates protective rubber cushioning at every point of impact. The frictionless can mechanism, with a limited life-time warranty, and all internal optical components, are shock mounted to maintain precise alignment under high shock loads. The scan window is made of shatter-proof material and is diamond coated to resist scratching. Even the replaceable interface cable is protected with an integrated metal strain relief.

Innovative Host Connectivity

The PowerScan scanner has a broad range of communication options using unique multi-interface modules, which allow for connection to most host computer systems. Our AutoSelect™ feature allows you to quickly move between different hosts and applications by simply changing cables. In addition PowerScan's low current draw, combined with its low power mode, make it ideal for use with battery operated terminals.



Specifications

PowerScan™

PRODUCT

Mechanical

Dimensions: 2.7 x 4.4 x 7.2" / 6.9 x 11.2 x 18.3 cm

Weight

Scanner: 9.9 ozs. / 280 g

Cable (32"/82.3 cm): 6.2 ozs. / 176 g

Cable length options

Collapsed: 32" / 81 cm,

Max. Working: 72" / 183 cm;

Collapsed: 80" / 203 cm,

Max. Working: 120" / 305 cm

(For other cable options, contact your PSC sales representative.)

Optical

Light source: Extra Bright 650nm

Visible Laser Diode (VLD)

Scan system: Frictionless lifetime flexure mechanism

Rate: 37 scans/sec. nominal

Depth-of-field: Refer to chart on this page

Print contrast ratio: 25% minimum

Pitch: ±65°

Skew: ±55°

Ambient light immunity

Artificial light: 1,200 foot candles / 12912 Lux

Sunlight: 8,000 foot candles / 86080 Lux

Electrical

Operating voltage: 4 VDC to 14 VDC

Operating current – nominal

Undecoded: 75mA @ 5 VDC

Decoded: 100mA @ 5 VDC

Idling current – low power mode:

<50µA @ 5 VDC

Environmental

Temperature rating

Operating: -22° to 122° F / -30° to 50° C

Storage: -40° to 158° F / -40° to 70° C

Humidity: 5 to 95% NC

Shock (at 23°C): withstands multiple 6.5' / 2 m drops to concrete

Vibration: meets MIL-STD-810E

Water & Dust: IEC529 rating IP54DW

Decoding Capability

(autodiscriminates between)

UPC A, E / EAN 8,13 / JAN 8, 13

(P2 / P5, Code 128 EAN add-ons)

Code 128

Codabar

Pharmacode 39

Code 39 Full ASCII

Code 39

Code 93

Interleaved 2 of 5

Standard 2 of 5

MSI / Plessey

BC412 (upon request)

Communications

Undecoded: Standard and Intermec-compatible

Multi-interface modules (interchangeable,

AutoSelect™ cable determines active interface):

RS232C / Standard Keyboard Wedge /

Wand Emulation

Universal Keyboard Wedge / RS232*

IBM 46XX / RS232C

*This RS232 interface only supports RXD and TXD, no control signals are available.

Safety & Regulatory

Electrical: Complies to Gost R; TÜV; UL; cUL

Emissions: Complies to FCC-A; EN 55022-B

BCIQ CNS13438; AS/NZS 3548; VCCI-B

Laser classification: CDRH Class II;



(CAUTION: Laser Radiation –

do not stare into beam);

IEC 60825 Class 2



Available Mount Options



P/N: 7-0477

AutoSense®

P/N: 7-0404

Take Up Reel

P/N: 7-0462

Universal Kit

P/N: 7-0430

Holster/Fork Lift

Depth-of-Field Chart – (printing resolution, contrast and ambient light dependent)		
Label Density	Standard (decoded) Range	High Density (decoded) Range
Paper Labels	3 mil	1.0" to 2.0" / 2.5 to 5.1 cm
	4 mil	1.0" to 2.0" / 2.5 to 8.0 cm
	5 mil	0.8" to 3.8" / 2.0 to 10.0 cm
	7.5 mil	0.6" to 4.5" / 1.5 to 11.0 cm
	10 mil	0.2" to 5.5" / 0.5 to 14.0 cm
	15 mil	
	20 mil	
	55 mil	

PSC Inc.

959 Terry Street

Eugene OR 97402-9150 USA

Tel: 800 695 5700 or 541 683 5700

Fax: 541 345 7140

Specifications are subject to change without notice.

Additional information concerning this product or other PSC products

and services can be found at the PSC website: www.pscnet.com,

or contact your PSC representative for more information.



PSC Worldwide Sales and Service locations

Australia - NSW

Tel: 61 2 9878 8999

Fax: 61 2 9878 8688

Australia

Tel: 61 3 9281 3288

Fax: 61 3 9243 5510

Belgium

Tel: 32 2 414 74 09

Fax: 32 2 410 11 63

Brazil

Tel: 55 11 5507 7721

Fax: 55 11 5507 7696

Chile

Tel: 562-339-7000

Fax: 562-339-7985

China

Tel: 86 10 6857 9048

Fax: 86 10 6857 8699

China - South

Tel: 86 20 8765 9955

Fax: 86 20 8765 9955

France

Tel: 33 1 64 86 71 00

Fax: 33 1 64 46 72 44

Germany

Tel: 49 6151 93580

Fax: 49 6151 93588

Hong Kong

Tel: 852 25846210

Fax: 852 25210291

India

Tel: 91 11 4621586

Fax: 91 11 4623305

Italy

Tel: 39 039 629031

Fax: 39 039 6859496

Japan

Tel: 81 3 3491 6761

Fax: 81 3 3491 6656

Latin America

Tel: 1 305 539 0111

Fax: 1 305 539 0206

Singapore

Tel: 65 435 1311

Fax: 65 226 1242

Spain

Tel: 34 91 203 65 00

Fax: 34 91 203 65 01

Sweden

Tel: 46 4010 84 92

Fax: 46 4010 84 91

Turkey

Tel: 90 212 23691 15

Fax: 90 212 23691 16

United Kingdom

Tel: 44 1923 809500

Fax: 44 1923 809505