

## **IMAGETEAM™ 4410 HD/HD10** *Hand Held 2D Image Readers*



### **Features**

*Supports All Popular 2D Symbologies - IT4410 supports all popular matrix and stacked linear symbologies: MaxiCode, Data Matrix, QR, and PDF417. Additional symbologies will be added as emerging codes are approved by AIM.*

*HHP Video Imaging Technology - HHP's over 20 years experience in developing video-based instruments for medical and industrial inspection is brought to 2D data collection systems.*

*Hand Held Reader - Opens up new 2D bar code and image capture possibilities in portable hand held and fixed scanning applications.*

*Omni-Directional Scanning - The video technology basis for the IT4410 means it can offer omni-directional scanning, even on linear codes, greatly simplifying operator training and increasing productivity.*

*Aiming - The IT4410 has a bright, intuitive aiming line.*

*Autodiscriminates Between Supported Symbologies and Fonts - Reads all major linear, stacked linear, and matrix bar codes, as well as machine readable fonts used in Optical Character Recognition (OCR).*

*2D Print Quality Assessment (PQA) - An easy and inexpensive approach to providing test results useful for 2D bar code symbol process control, and improvement of the overall 2D data acquisition system.*

The HHP IMAGETEAM™ (IT) 4410 High Density Image Reader is a hand held input device for reading and decoding two dimensional (2D) symbologies. The IT4410 offers integrated support for Matrix, stacked linear, and conventional linear bar codes, as well as a single line of OCR-A and OCR-B fonts. Multi-line OCR applications can also be read. The IT4410 is designed for reading high density matrix symbols. The IT4410 has the power to capture and download images to a PC for applications, such as signature capture, PC-based decoding, and image lift requirements.

Lightweight, balanced, and easy to use, the IT4410 can be used in repetitive, high volume hand scanning operations in even the most demanding environments. The IT4410 can be configured for keyboard wedge, Non Decoded Laser Output (Code 128 emulation), TTL, or True RS-232. The IT4410 connects to all popular PCs and portable data terminals. The Non Decoded Laser Output mode can be used with external wedge decoders and portable terminals or other devices without 2D decoding capability. The IT4410 can be integrated with all types of customer systems.

The IT4410 features integrated processing for a one-piece scanning solution - no additional boxes or electronics needed. The reader provides omnidirectional and auto-discrimination decoding for symbologies, such as MaxiCode, PDF417, QR, Data Matrix, Aztec code, RSS code, composite codes, postal codes, Code 39, Code 93, Interleaved 2 of 5, Codabar, Code 128, UPC, and EAN. Additional symbologies will be added based on market demand.

Because the IT4410 is a fixed focus device, four product models with different focal points are available. Two high density scanners are available: IT4410HD and IT4410HD10. The IT4410HD, with a focal point of 2 inches, is recommended when the matrix symbols are less than 10 mil. The IT4410HD10 is recommended for applications when the matrix codes are greater than 10 mil. This version, with a focal point of 3 inches, maximizes the depth of field on 10 mil matrix codes, which directly correlates to greater functionality by the end user. The long range (LR/LX) models of the IT4410 are highlighted in a separate data sheet.

**Upgrade your image.**

# IMAGETEAM™ 4410 HD/HD10 Specifications

## Performance

**HD Focal Point:** 2 inches from nose  
**HD10 Focal Point:** 3 inches from nose

<b>HD Working Range:</b> (typical)	<b>6 pt OCR</b>	<b>6.6 mil QR</b>	<b>6.6 mil Data Matrix</b>	<b>4 mil Linear</b>
	<b>20 cpi</b>	<b>(.017 cm)</b>	<b>(.017 cm)</b>	<b>(.01 cm)</b>
	<b>Near</b>	2 in. (5.1 cm)	1.7 in. (4.3 cm)	1.7 in. (4.3 cm)
<b>Far</b>	3.5 in. (8.9 cm)	2.45 in. (6.2 cm)	2.45 in. (6.2 cm)	2.7 in. (6.9 cm)

<b>HD10 Working Range:</b> (typical)	<b>10 mil QR</b>	<b>10 mil Data Matrix</b>	<b>5 mil Linear</b>
	<b>(.025 cm)</b>	<b>(.025 cm)</b>	<b>(.013 cm)</b>
	<b>Near</b>	2.0 in. (5.1 cm)	2.2 in. (5.6 cm)
<b>Far</b>	4.0 in. (10.2 cm)	3.8 in. (9.6 cm)	3.75 in. (9.5 cm)

**Rotational Sensitivity:** 360°  
**Viewing Angle:** ±45°  
**Ambient Light:** Total darkness to 100,000 lux (full sunlight)  
**Aiming:** 660nm LEDs provide bright aiming line

## Symbologies

**2 Dimensional:** MaxiCode, PDF417, MicroPDF417, Aztec, Aztec Mesa, Data Matrix, QR Code, Code 49, UCC Composite, Snowflake\*, Vericode\*, Dataglyphs\*

**Linear:** Code 39, Code 128, Codabar, UPC, EAN, I 2 of 5, RSS, BC 412\*, Code 93, Codablock  
\* available to licensed users only

**Postal:** Postnet (US), BPO4 State, Canadian 4 State, Japanese Post, KIX (Dutch Post), Planet Code

**OCR Fonts:** OCR-A, OCR-B

**Interfaces:** RS232, Wedge, and HHLC (Code 128 Emulation)

**Programmable Options:** Baud, Parity, Data Formatting, Code Options

## Mechanical/Electrical

### Dimensions

**Length:** 6.1 in. (15.4 cm)  
**Height:** 5.6 in. (14.2 cm)  
**Width:** 2.5 in. (6.4 cm)  
**Weight w/o cord:** 7 oz. (198 g) or less  
**Power Requirements:** 4 to 9 volts  
**Current Draw:** Lower Power Mode - average @ 5 VDC-40mA  
Medium Power Mode - average @ 5 VDC-125mA  
High Power Mode - average @ 5 VDC-175mA  
**Standby Current:** < 200µA @ 5V

## Environmental

**Temperature**  
**Operating:** -0°C to 50°C  
**Storage:** -40°C to +70°C

**Humidity:** 95% RH, non condensing at 50°C

**Shock:** 10 drops 5 ft. to concrete @ room temperature

**ESD:** Functional after 15KV discharge

**Agency:** FCC Class B, CE

**Seal Rating:** IP52



Complies with EMC 89/336/EEC  
and LVD 73/23/EEC

## Worldwide Offices

**Offices Serving North America**  
Skaneateles Falls, NY  
Tel: +1 315 685 8945  
or, in North America: +1 800 782 4263  
sales@hhp.com  
Charlotte, NC  
Tel: +1 704 998 3998  
or, in North America: +1 800 782 4263  
sales@hhp.com

**Offices Serving Europe, Middle East, and Africa**  
Europe  
Tel: +31 (0) 40 29 01 600  
euro\_sales@hhp.com  
United Kingdom  
Tel: +44 (0) 1 925 240055  
euro\_sales@hhp.com  
Ireland  
Tel: +353 (0) 502 44007  
euro\_sales@hhp.com

**France**  
Tel: +33 (0) 1 461 04111  
euro\_sales@hhp.com  
**Germany**  
Tel: +49 (0) 7 477 151377  
euro\_sales@hhp.com  
**Spain**  
Tel: +34 93 228 76 68  
euro\_sales@hhp.com

**Offices Serving Asia and the Pacific Rim**  
**Hong Kong**  
Tel: +852 2511 3050/2511 3132  
asia\_sales@hhp.com  
**Japan**  
Tel: +813 52127392  
asia\_sales@hhp.com

**Offices Serving Latin America**  
**Naples, Florida**  
Tel: +1 239 263 7600  
la-sales@hhp.com  
**São Paulo**  
Tel: +55 11 5016 3454  
la-sales@hhp.com  
**Rio De Janiero**  
Tel: +55 21 2494 7060  
la-sales@hhp.com

Web Site Address [www.hhp.com](http://www.hhp.com)

Hand Held Products, Inc. d/b/a HHP ("HHP") © 1999-2002. All rights reserved. Printed in the U.S.A.

Due to HHP's continuing product improvement programs, specifications and features herein are subject to change without notice.