

Product Profile



- Supercharged Output**
The EasyCoder 501 XP printer combines remarkably fast throughput and speed with high resolution. The EasyCoder 501 XP is the first printer in the industry to offer 12 ips at 300 dpi resolution.
- Minimal Downtime**
Designed to make media changes faster and easier, the EasyCoder 501 XP speeds the process of changing the labels and ribbons with Intermec's Open Web Path for quick label and ribbon loading.
- Intelligent**
Printer integration is made easy with Fingerprint™ programming language. Standard with each printer, Fingerprint allows the printer to easily adapt to your existing system without reinvesting time and money.
- Rugged Design**
Like most Intermec printers, the EasyCoder 501 XP is rugged. The aluminum and steel design ensures continuous performance even in the harshest environments.

E A S Y C O D E R ® 5 0 1 X P P R I N T E R

When an entire roll of labels needs to be printed now. When applications demand "first label out" at breakneck speed. When there is no time to waste, the EasyCoder 501 XP delivers.

With its 32 bit RISC processor and 12 ips print speed, no other printer on the market delivers the exceptional print quality obtained with a 300 dpi printhead at the speed today's businesses demand.

Intermec has introduced several features into the EasyCoder 501 XP; all designed to make life for the operator simpler. The EasyCoder 501 XP features an Open Web Path for quick loading of media and ribbon. The patented Magnet QuickMount printhead requires no tools and no technician for replacement. The EasyCoder 501 XP

is designed to easily integrate into existing printer applications utilizing non-Intermec printers. Through Intermec's Fingerprint programming language, host-programming changes need not occur. Because the EasyCoder 501 XP printers come equipped with the Fingerprint printer language, the printer can be programmed to interpret and translate different device data streams. This all adds up to easier decision making when it comes to upgrading to newer and faster technology or replacing old antiquated technology.

The EasyCoder 501 XP along with its 15.24 cm (6in) wide counterpart, the EasyCoder 601 XP, gives your organization the necessary edge, to keep one step ahead in today's fast-paced world.

General

Direct Thermal and Thermal Transfer printer for self-adhesive labels, tickets and tags. Peel-off, internal rewind of backing paper is optional.

Model

EasyCoder 501XP

Physical Characteristics

Length: 480 mm (18.9 in)
Height: 239 mm (9.4 in)
Width: 275 mm (10.8 in)
Weight: 13 kg (28.7 lbs)

Print Specifications**Print Width:**

Max. 106,6 mm (4.2 in)

Print Speed:

Variable speed 100–300mm/s(4–12in/s) at 300 dpi.
True speed equivalent to 30 ppm, A4 at 300 dpi.

Print Direction:

Prints smooth text, any size bar codes, and graphics in all four directions.

Print Resolution:

300 dpi (12 dots/mm)

Media Specifications**Label Size –**

Max width: 120 mm (4.7 in)

Max length: 400 mm (15.7 in) with standard DRAM memory

Label/Ribbon Roll –

Label roll: max. diameter 205 mm (8 in)

Ribbon roll: max. length 450 m (1476 ft)

Media Core: 38–40 mm (1.5–1.6 in) and 75 mm (3 in)

Media/Ribbon Characteristics –

Style: Roll-fed, die-cut, continuous, or fanfold labels, tags or tickets

Type: Plain paper thermal transfer or thermal sensitive papers

Ribbon Type: Wax, wax/resin, resin

Paper/Ribbon Setup: EasySet System—built-in bar code wand interface offers instant printer setting for various papers, ribbons and other printer parameters.

Software**Printer language:**

Fingerprint or Intermec Direct Protocol.

Windows™ label program:

Windows printer drivers for Windows 3.11, Windows 95, 98 & NT.

Bar Code Symbolologies

Incorporates 37 bar code symbolologies, including 2-Dimensional codes.

Characters/Fonts

TrueDoc™ and TrueType™ font capability.

All fonts are scalable. Font cache for maximum performance. 15 UNICODE scalable Latin fonts are standard. Non-Latin fonts for Eastern Europe, the Middle East and Asia are optional. Printing of graphics and symbols is also easy.

Environment

+5° to 40°C (+40° to +104°F)

Humidity

20–80% non-condensing (also depend-ing on label material).

Power Supply

Power Factor Correction (PFC). Switches automatically between 115 V or 230 VAC, 45 or 65 Hz. Voltage range: 90–264 VAC. PFC regulation.

Memory

Faster execution with new Mips 32 bit RISC processor.

Standard: 2MB Flash
4MB DRAM
1 PC card slot

Optional: max. 8MB DRAM
max. 6MB Flash
max. 8MB PC card

Interface

Standard: RS-232, Fast Centronics
Baud Rate 300–38400

Optional: Industrial I/O Relays,
DIDO, RS-232, RS-422

Protocol

XON/XOFF, ENQ/ACK, DTR, RTS/CTS.

Display

Back-lit LCD for 2x16 characters and 3 LED indicator lamps.

Keyboard

Membrane-switch keyboard (0–9) and 13 other function keys.

Real Time Clock (RTC)

Standard.

AWS

Intermec's Anti Wrinkle System prevents ribbon wrinkling, secures print quality.

Regulatory Approvals

CE (EN55022 Class B), FCC Class A, UL, CSA, C-Tick

Options

Peel-off/Self-strip, integral Self-strip unit with Liner Takeup, Label-Taken Sensor (LTS), Ribbon Low Sensors, Label Roll Retainer, Cutter, Fan-Fold guides, PC Flash Card memory, Flash SIMM and DRAM SIMM memory, Non-Latin fonts, EasySet bar code Wand, External RE 232C Alphanumeric Keyboard, Industrial Interface.

North America

Corporate Headquarters
6001–36th Avenue West,
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551

Systems & Solutions
550 – 2nd Street S.E.,
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453

Media Supplies
9290 Le Saint Drive,
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487

**Europe/
Middle East & Africa**

Headquarters
Sovereign House, Vastern Rd,
Reading, Berkshire RG1 8BT,
United Kingdom
tel: +44.118.987.9400
fax: +44.118.987.9401

Benelux
tel: +31.243723100
fax: +31.243723195

Denmark
tel: +45.4816.6166
fax: +45.4816.6167

Finland
tel: +35.8952.3721
fax: +35.8952.9224

France
tel: +33.130.152.535
fax: +33.134.801.433

Germany
tel: +49.211.536.010
fax: +49.211.536.0150

Italy
tel: +39.026.624.051
fax: +39.026.624.0558

Norway
tel: +47.6791.1710
fax: +47.6791.1711

Spain
tel: +34.913.832.252
fax: +34.913.832.247

Sweden
tel: +46.8622.0660
fax: +46.8622.0661

United Kingdom
tel: +44.118.923.0800
fax: +44.118.923.0801

**Asian Pacific/
Latin America**

Hong Kong
tel: +85.225.749.777
fax: +85.225.749.725

Singapore
tel: +65.324.8391
fax: +65.324.8393

Australia
tel: +61.299.012.065
fax: +61.299.546.300

South America and Mexico
tel: +1.949.975.1905
fax: +1.949.975.1913

**Worldwide
Fax Document
Retrieval Service**

800.755.5505
(North America Only)
tel: 650.556.8447

Internet
www.intermec.com

Sales
800.347.2636
(toll free in N.A.)
425.348.2726

Service and Support
800.755.5505
(toll free in N.A.)
425.356.1799

Copyright © 2001 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners.

Printed in Sweden.
Part No. 1-962028-01
01/03

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.